

Visilift Visi 58 Specifications

General	
Classification	Residential - Single Family
Applied Code	ASME 17.1-2004 Section 5.3
Number of Floors	2 - 4
Capacity	840 lbs. (381.02 kg)
Net Platform Size	13.28 Square Feet
Speed	30 Feet Per Minute
Maximum Travel	40 Feet
Walls	Acrylic - ANSI z97.1
Manufacturer	Visilift, LLC Windsor, Colorado
Drive Unit / Suspension	
Type	Winding Drum
	Aircraft Cable 2 @ 3/8" Dia. 7X19 IWRC
	14,400 lbs. per Cable Nominal Strength
Motor	1.5 HP with Integral Brake
Controller	Pre-Programmed Variable Frequency Drive UL# E317989
Door Interlocks	Electro Mechanical Interlock UL# SA13369

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VISILIFT, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VISILIFT, LLC IS PROHIBITED.</p>			<p>DIMENSIONS ARE IN INCHES</p> <p>TOLERANCES:</p> <p>FRACTIONAL ±</p> <p>ANGULAR: MACH ± BEND ±</p> <p>TWO PLACE DECIMAL ±</p> <p>THREE PLACE DECIMAL ±</p>		NAME	DATE	<p>VISILIFT, LLC</p> <p>Visi 58 Specifications</p> <p>VISI 58</p>		
					DRAWN				
					CHECKED				
					ENG APPR.				
					MFG APPR.				
					Q.A.				
					COMMENTS:				
		MATERIAL							
		FINISH							
	NEXT ASSY	USED ON					SIZE	DWG. NO.	REV.
							A	Visi 58 Specifications	11/19/2009
	APPLICATION		DO NOT SCALE DRAWING				SCALE:1:1	WEIGHT:	SHEET 1 OF 1