

Freedom Series Comparison Chart

Enhance your home and elevate its value with Nationwide Lifts' Freedom Series of home elevators. The Freedom series offers traditional design coupled with state-of-the-art craftsmanship to ensure that you'll be free to enjoy unsurpassed quality and lasting convenience for years to come.

The Freedom series of home lifts allows you to join luxury and functionality in perfect unison with a broad spectrum of design options and the freedom to customize such a rich and welcoming addition to your home.

	Freedom 750	Freedom 950	Freedom Green	Freedom 1500	Freedom Commercial
Capacity (Up to)	750 or 1000 lbs	750 or 950 lbs	750 or 950 lbs	1500 lbs	1400 lbs
Wall Finishes	Melamine, Recessed Veneer, Raised Hardwood	Melamine, Recessed Veneer, Raised Hardwood	Melamine, Recessed Veneer, Raised Hardwood	Melamine, Stainless Steel, Raised Hardwood	Painted Steel or Plastic Laminate
Fixture Finishes	Stainless Steel or Brass	Stainless Steel or Brass	Stainless Steel or Brass	Stainless Steel or Brass	Stainless Steel or Brass
Standard Sizes	(a) 36" x 48" (b) 36" x 54" (c) 36" x 60"	(a) 36" x 48" (b) 36" x 54" (c) 36" x 60"	(a) 36" x 48" (b) 36" x 54" (c) 36" x 60"	(a) 45" x 48" (b) 45" x 54" (c) 45" x 60"	(a) 48" x 54" (b) 42" x 60"
Space Required	(a) 51" x 56" (b) 51" x 62" (c) 51" x 68"	(a) 50" x 56" (b) 50" x 62" (c) 50" x 68"	(a) 50" x 56" (b) 50" x 62" (c) 50" x 68"	(a) 64" x 62" (b) 64" x 68" (c) 64" x 74"	(a) 69" x 73" (b) 69" x 79"
Lift Mechanism	Hydraulic	Winding Drum	Traction Machine	Hydraulic	Hydraulic
Machine Room	Yes	Not Required	Not Required	Yes	Yes
Indoor\Outdoor	Indoor	Indoor	Indoor	Indoor	Indoor
Maximum # of Stops	5 Stops	5 Stops	5 Stops	5 Stops	4 Stops
Maximum Vertical Travel	50'	50'	50'	50'	25'
Vertical Travel Speed	36 fpm	30 fpm	40 fpm	45 fpm	30 fpm
Contractor Prep	Hoistway Construction, Landing Doors & Power Supply	Hoistway Construction, Landing Doors & Power Supply	Hoistway Construction, Landing Doors & Power Supply	Hoistway Construction, Landing Doors & Power Supply	Hoistway Construction, Landing Doors & Power Supply
Pit Requirements	8" Minimum	8" Minimum	6" Minimum	12" Minimum	14" Minimum
Power Requirements	230V 30A (single phase)	230V 30A (single phase)	230V 20A (single phase)	230V 30A (single phase)	230V 50A (single phase)

DO NOT frame to these dimensions. Site specific drawings will be provided.